


1. Part No. Expression:

PICQ1707HP1R0MF

(a) (b) (c) (d) (e)(f)

- a) Series Code
- b) Dimension Code
- c) Type Code
- d) Inductance Code
- e) Tolerance Code
- f) RoHS Compliant

2. Configuration & Dimensions:




Note:

1. The above PCB layout is for reference only.
2. Solder paste thickness of 0.17mm and above is recommended.
3. Marking : Top row – Inductance code, Bottom row – Year/World week


Unit: mm

A	A'	B	C	D	E	T	L	G	H
17.6±0.4	16.9±0.3	16.9±0.3	6.7±0.3	2.1±0.3	11.9±0.3	0~+0.25	18.5 Ref.	12.2 Ref.	12.5 Ref.

3. Schematic:



4. Material List:



- (a) Core
- (b) Wire
- (c) Terminal
- (d) Ink
- (e) Paint

NOTE: Specifications subject to change without notice. Please check our website for latest information.

5. General Specification:

- (a) Reliability test for this part meets AEC-Q200 standard.
- (b) Operating Temp. : -55°C to +125°C(including self-temperature rise).
- (c) Storage Temp. : -55°C to +125°C (on board).
- (d) Humidity Range. : 85 ± 3% RH.
- (e) Heat Rated Current (I_{rms}) will cause the coil temperature rise approximately Δt of 40°C.
- (f) Saturation Current (I_{sat}) will cause L0 to drop approximately 30%.
- (g) Part Temperature (Ambient+Temp. Rise). : Should not exceed 125°C under worst case operating conditions.
- (h) Storage condition (component in its packaging)
 - i) Temperature: Less than 40°C
 - ii) Humidity : 60% RH

6. Electrical Characteristics:

Part Number	Inductance L0 (uH) ±20% @ 0 A	Test Frequency, (Hz)	I _{rms} (A) Typ.	I _{sat1} (A) Typ.	I _{sat2} (A) Typ.	DCR (mΩ) Typ. @25°C	DCR (mΩ) Max. @25°C
PICQ1707HPR45MF	0.45	1.0V/100K	62.0	85.0	125	0.80	0.96
PICQ1707HPR47MF	0.47	1.0V/100K	62.0	80.0	123	0.95	1.03
PICQ1707HP1R0MF	1.00	1.0V/100K	52.0	60.0	70.0	1.60	2.00
PICQ1707HP1R3MF	1.30	1.0V/100K	49.0	54.0	67.0	1.70	2.30
PICQ1707HP1R5MF	1.50	1.0V/100K	47.0	52.0	65.0	2.00	2.50
PICQ1707HP1R8MF	1.80	1.0V/100K	45.0	49.0	63.0	2.10	2.50
PICQ1707HP2R2MF	2.20	1.0V/100K	43.5	47.0	62.0	2.40	2.70
PICQ1707HP3R3MF	3.30	1.0V/100K	28.0	45.0	54.0	3.50	3.90
PICQ1707HP4R7MF	4.70	1.0V/100K	25.0	41.0	50.0	4.80	5.50
PICQ1707HP5R6MF	5.60	1.0V/100K	21.0	40.0	45.0	5.80	7.05
PICQ1707HP6R8MF	6.80	1.0V/100K	19.0	32.0	39.0	8.40	9.20
PICQ1707HP7R4MF	7.40	1.0V/100K	18.5	27.0	34.0	8.80	9.70
PICQ1707HP8R2MF	8.20	1.0V/100K	18.0	25.0	31.0	9.60	10.8
PICQ1707HP100MF	10.0	1.0V/100K	16.5	24.0	29.0	11.8	13.0
PICQ1707HP150MF	15.0	1.0V/100K	12.5	23.0	27.0	17.8	20.5

NOTE: Specifications subject to change without notice. Please check our website for latest information.




Part Number	Inductance L0 (uH) ±20% @ 0 A	Test Frequency, (Hz)	I rms (A) Typ.	I sat1 (A) Typ.	I sat2 (A) Typ.	DCR (mΩ) Typ. @25°C	DCR (mΩ) Max. @25°C
PICQ1707HP220MF	22.0	1.0V/100K	12.0	18.0	23.0	25.1	26.5
PICQ1707HP330MF	33.0	1.0V/100K	10.7	15.0	20.0	38.0	44.0
PICQ1707HP390MF	39.0	1.0V/100K	9.20	11.0	18.0	40.0	48.0
PICQ1707HP470MF	47.0	1.0V/100K	8.70	9.50	16.0	48.0	55.0
PICQ1707HP560MF	56.0	1.0V/100K	7.80	9.00	15.0	54.0	62.0
PICQ1707HP680MF	68.0	1.0V/100K	7.00	8.00	13.0	68.0	80.0
PICQ1707HP820MF	82.0	1.0V/100K	5.70	7.00	12.0	87.0	100
PICQ1707HP101MF	100	1.0V/100K	5.30	6.50	12.0	102	118

Note:


1) Isat Typ. and I rms Typ. value is derived based from accounting the upper limit tolerance into the inductance value.

7. Characteristics Curves:




NOTE: Specifications subject to change without notice. Please check our website for latest information.


PICQ1707HP2R2MF




PICQ1707HP3R3MF




PICQ1707HP4R7MF




PICQ1707HP5R6MF




PICQ1707HP6R8MF




PICQ1707HP7R4MF




PICQ1707HP8R2MF




PICQ1707HP100MF




PICQ1707HP150MF




PICQ1707HP220MF



PICQ1707HP330MF




PICQ1707HP390MF




NOTE: Specifications subject to change without notice. Please check our website for latest information.




PICQ1707HP470MF




PICQ1707HP560MF




PICQ1707HP680MF



PICQ1707HP820MF



PICQ1707HP101MF



NOTE: Specifications subject to change without notice. Please check our website for latest information.



8. Soldering:

Mildly activated rosin fluxes are preferred. The minimum amount of solder can lead to damage from the stresses caused by the difference in coefficients of expansion between solder, chip and substrate. Our terminations are suitable for all re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air.

8-1 Solder Re-flow:


Recommended temperature profiles for re-flow soldering in Figure 1.

8-2 Soldering Iron (Figure 2):

Products attachment with soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended.


Note :

- a) Preheat circuit and products to 150°C.
- b) 355°C tip temperature (Max.)
- c) Never contact the ceramic with the iron tip
- d) 1.0mm tip diameter (Max.)
- e) Use a 20 watt soldering iron with tip diameter of 1.0mm
- f) Limit soldering time to 4~5 secs.



Reflow times: 3 times max.

Fig.1



Iron Soldering times: 1 times max.


Fig.2

NOTE: Specifications subject to change without notice. Please check our website for latest information.




9. Packaging Information:

9-1 Reel Dimension



Type	A(mm)	B(mm)	C(mm)	D(mm)
13"x32mm	32.4+2/-0	100±2	13.0+0.5/-0.2	330

9-2 Tape Dimension




Series	Size	Bo(mm)	B1(mm)	Ao(mm)	A1(mm)	Ko(mm)	P(mm)	P0(mm)	P2(mm)	W(mm)	E(mm)	F(mm)	t(mm)	D(mm)
PICQ	1707	18.5±0.1	17.5±0.1	17.5±0.1	12.6±0.1	7.5±0.1	24±0.1	4.0±0.1	2.0±0.05	32±0.3	1.75±0.1	14.2±0.1	0.5±0.05	1.5±0.1

9-3 Packaging Quantity

PICQ	1707
Chip / Reel	200
Inner box	200
Carton	800

NOTE: Specifications subject to change without notice. Please check our website for latest information.

9-4 Tearing Off Force



The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed mm/min
5~35	45~85	860~1060	300

Application Notice:

1. Storage Conditions:

To maintain the solderability of terminal electrodes:

- a) Recommended products should be used within 12 months from the time of delivery.
- b) The packaging material should be kept where no chlorine or sulfur exists in the air.

2. Transportation:

- a) Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- b) Vacuum pick up is strongly recommended for individual components.
- c) Bulk handling should ensure that abrasion and mechanical shock are minimized.

NOTE: Specifications subject to change without notice. Please check our website for latest information.

