

1. Part No. Expression:

P I F Q 0 4 0 2 A R 2 2 M N

(a) (b) (c) (d) (e)(f)

a) Series Code

b) Dimension Code


c) Type Code

d) Inductance Code

e) Tolerance Code

f) Internal Controlled Code

2. Configuration & Dimensions:




Note:

1. The above PCB layout is for reference only.
2. Solder paste thickness of 0.12mm and above is recommended.
3. Marking: Top row- Inductance code, Bottom row-YYWW.


Unit: mm

A	B	C	D	E	F	L	G	H
4.10±0.2	4.10±0.2	1.90±0.2	3.40±0.3	0.88±0.2	1.60±0.25	3.40 Ref.	1.40 Ref.	3.80 Ref.

3. Schematic:



4. Material List:



(a) Core

(b) Wire

(c) Solder

(d) Ink

NOTE: Specifications subject to change without notice. Please check our website for latest information.



5. General Specification:

- (a) Reliability test for this part meets AEC-Q200 standard.
- (b) Operating Temp. : -55°C to +155°C (including self-temperature rise).
- (c) Storage Temp.: -55°C to +155°C (on board).
- (d) Heat Rated Current (Irms) will cause the coil temperature rise approximately Δt of 20°C & 40°C (see following table).
- (e) Saturation Current (Isat) will cause L0 to drop approximately 30%.
- (f) Part Temperature (Ambient + Temp. Rise): Should not exceed 155°C under worst case operating conditions.
- (g) Rated Operating Voltage. :
 - i) (across inductor) 15V Ref. (1.5uH and below).
 - ii) (across inductor) 40V Ref. (0.1uH and above).
- (h) Storage condition (component in its packaging)
 - i) Temperature: Less than 40°C
 - ii) Humidity: 60% RH

6. Electrical Characteristics:

Part Number	Inductance (uH) $\pm 20\%$ @ 0 A	Test Frequency (Hz)	I rms(A) Typ.		I sat(A)		DCR (m Ω) Typ.	DCR (m Ω) Max.
			@20°C	@40°C	Typ.	Max.		
PIFQ0402AR10MN	0.10	0.1V/100K	13.5	18.0	38.0	33.0	2.2	2.42
PIFQ0402AR22MN	0.22	0.1V/100K	13.0	16.8	19.5	18.8	4.1	4.6
PIFQ0402AR36MN	0.36	0.1V/100K	11.0	14.5	17.0	15.0	5.6	6.3
PIFQ0402AR40MN	0.40	0.1V/100K	10.0	14.0	15.5	13.5	6.9	7.73
PIFQ0402AR56MN	0.56	0.1V/100K	8.5	12.0	14.0	12.6	8.4	9.3
PIFQ0402AR60MN	0.60	0.1V/100K	8.0	11.7	13.7	12.3	8.6	9.52
PIFQ0402AR72MN	0.72	0.1V/100K	7.6	10.5	12.0	10.6	10.4	11.6
PIFQ0402A1R0MN	1.00	0.1V/100K	6.8	9.6	9.6	8.8	13.3	14.6
PIFQ0402A1R2MN	1.20	0.1V/100K	6.6	9.0	9.0	7.8	16.2	17.9
PIFQ0402A1R5MN	1.50	0.1V/100K	5.8	7.6	8.0	7.4	21.0	23.5
PIFQ0402A1R8MN	1.80	0.1V/100K	5.2	7.0	7.5	7.0	25.0	28.0
PIFQ0402A2R2MN	2.20	0.1V/100K	4.6	5.6	6.5	6.0	35.2	38.7


Notes:

- 1) Isat Typ. and Irms Typ. value is derived based from accounting the upper limit tolerance into the inductance value
- 2) At all times, the current supplied to the product should not exceed Isat Max. value.

NOTE: Specifications subject to change without notice. Please check our website for latest information.



7. Characteristics Curves:



NOTE: Specifications subject to change without notice. Please check our website for latest information.



8. Soldering:

Mildly activated rosin fluxes are preferred. The minimum amount of solder can lead to damage from the stresses caused by the difference in coefficients of expansion between solder, chip and substrate. Our terminations are suitable for all re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air.

8-1 Solder Re-flow:

Recommended temperature profiles for re-flow soldering in Figure 1.


8-2 Soldering Iron (Figure 2):

Products attachment with soldering iron is discouraged due to the inherent process control limitations.

In the event that a soldering iron must be employed the following precautions are recommended.


Note :

- a) Preheat circuit and products to 150°C.
- b) 355°C tip temperature (Max.)
- c) Never contact the ceramic with the iron tip
- d) 1.0mm tip diameter (Max.)
- e) Use a 20 watt soldering iron with tip diameter of 1.0mm
- f) Limit soldering time to 4-5 secs.



Reflow times: 3 times max.

Fig.1



Iron Soldering times: 1 times max.


Fig.2

NOTE: Specifications subject to change without notice. Please check our website for latest information.




9. Packaging Information:

9-1 Reel Dimension



Type	A(mm)	B(mm)	C(mm)	D(mm)
13"x12mm	12.4 +2/-0	100±2	13.0 +0.5/-0.2	330

9-2 Tape Dimension



Series	Size	Ao(mm)	Bo(mm)	Ko(mm)	P(mm)	W(mm)	F(mm)	T(mm)	D(mm)
PIFQ	0402	4.4±0.1	4.4±0.1	2.3±0.1	8.0±0.1	12.0±0.3	5.5±0.1	0.35±0.1	1.5±0.1


9-3 Packaging Quantity

PIFQ	0402
Chip / Reel	3000
Inner box	6000
Carton	24000

NOTE: Specifications subject to change without notice. Please check our website for latest information.



9-4 Tearing Off Force



The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed mm/min
5~35	45~85	860~1060	300

Application Notice:

1. Storage Conditions:

To maintain the solderability of terminal electrodes:

- a) Recommended products should be used within 12 months from the time of delivery.
- b) The packaging material should be kept where no chlorine or sulfur exists in the air.

2. Transportation:

- a) Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- b) Vacuum pick up is strongly recommended for individual components.
- c) Bulk handling should ensure that abrasion and mechanical shock are minimized.

NOTE: Specifications subject to change without notice. Please check our website for latest information.

