


1. Part No. Expression

PIC1206HPR47MF

(a) (b) (c) (d) (e) (f)

- | | |
|--------------------|---------------------|
| (a) Series Code | (d) Inductance Code |
| (b) Dimension Code | (e) Tolerance Code |
| (c) Material Code | (f) Packaging Code |

2. Configuration & Dimensions (Unit: mm)




Recommended PCB Layout

- Note:
1. The above PCB layout reference only.
 2. Recommend solder paste thickness at 0.15 mm and above.
 3. Marking: Top= Inductance Code, Bottom=YYWW (Year/World week), Black


A	B	C	D	E	G	H	L
13.5±0.5	12.5±0.3	5.7±0.3	2.3±0.3	4.7±0.3	8.0 Ref	5.0 Ref	14.2 Ref

NOTE: Specifications subject to change without notice. Please check our website for latest information.

3. Schematic



4. Material List



- (a) Core
- (b) Wire
- (c) Clip
- (d) Paint
- (e) Ink

5. General Specifications

- (a) Operating Temp.: -40°C to +125°C (including self-temperature rise)
- (b) Storage Temp.: -40°C to +125°C (on board)
- (c) All test data referenced to 25°C ambient.
- (d) Heat Rated Current (I_{rms}) will cause the coil temperature rise approximately ΔT of 40°C.
- (e) Saturation Current (I_{sat}) will cause inductance L₀ to drop approximately 30%.
- (f) Part Temperature (Ambient + Temp. Rise): Should not exceed 125°C under worst case operating conditions.
- (g) Maximum Operating Voltage: 80V
- (h) Storage Condition (Component in its packaging)
 - i) Temperature: Less than 40°C
 - ii) Humidity: Less than 60% RH

NOTE: Specifications subject to change without notice. Please check our website for latest information.

6. Electrical Characteristics


Part Number	Inductance (μ H) @0A \pm 20%	Test Frequency	I _{rms} (A) Typ	I _{sat1} (A) Typ	I _{sat2} (A) Typ	DCR (m Ω)	
						Typ	Max
PIC1206HPR47MF	0.47	1.0V/100KHz	38	60	64	0.92	1.3
PIC1206HPR56MF	0.56	1.0V/100KHz	35	56	60	1.15	1.5
PIC1206HPR68MF	0.68	1.0V/100KHz	33	53	57	1.33	1.7
PIC1206HP1R0MF	1.00	1.0V/100KHz	29	45	53	1.8	2.4
PIC1206HP1R2MF	1.20	1.0V/100KHz	28	44	51	2.1	2.8
PIC1206HP1R5MF	1.50	1.0V/100KHz	26	43	50	2.7	3.2
PIC1206HP2R2MF	2.20	1.0V/100KHz	21	34	43	4.0	4.7
PIC1206HP2R7MF	2.70	1.0V/100KHz	19	31	40	4.6	5.4
PIC1206HP3R3MF	3.30	1.0V/100KHz	17	28	35	5.8	7.1
PIC1206HP4R7MF	4.70	1.0V/100KHz	16	25	30	9.5	11.5
PIC1206HP5R6MF	5.60	1.0V/100KHz	15.5	22	28	10.8	12.6
PIC1206HP6R8MF	6.80	1.0V/100KHz	15	19	25	12	13.8
PIC1206HP8R2MF	8.20	1.0V/100KHz	11	17	23	13.6	16
PIC1206HP100MF	10.0	1.0V/100KHz	11	15.5	21	18	20.7
PIC1206HP120MF	12.0	1.0V/100KHz	9.5	13.5	18	20	23
PIC1206HP150MF	15.0	1.0V/100KHz	9.0	13	16	25	29
PIC1206HP180MF	18.0	1.0V/100KHz	8.5	12	15	30	35
PIC1206HP220MF	22.0	1.0V/100KHz	8.0	11	14	34	39.5
PIC1206HP270MF	27.0	1.0V/100KHz	7.0	9.0	13	49	56
PIC1206HP330MF	33.0	1.0V/100KHz	6.0	8.0	12.0	65	75
PIC1206HP470MF	47.0	1.0V/100KHz	5.5	7.0	11.0	80	90
PIC1206HP560MF	56.0	1.0V/100KHz	5.3	6.5	10	101	118
PIC1206HP680MF	68.0	1.0V/100KHz	5.0	6.0	9.0	120	140
PIC1206HP820MF	82.0	1.0V/100KHz	4.5	5.5	8.5	138	161
PIC1206HP101MF	100	1.0V/100KHz	4.0	5.0	8.0	180	200
PIC1206HP121MF	120	1.0V/100KHz	3.5	4.5	7.0	210	235
PIC1206HP151MF	150	1.0V/100KHz	3.0	4.0	6.0	300	350

NOTE: Specifications subject to change without notice. Please check our website for latest information.




7. Characteristics Curve


PIC1206HPR47MF




PIC1206HPR56MF




PIC1206HPR68MF




PIC1206HP1R0MF



PIC1206HP1R2MF




PIC1206HP1R5MF




NOTE: Specifications subject to change without notice. Please check our website for latest information.


PIC1206HP2R2MF




PIC1206HP2R7MF




PIC1206HP3R3MF




PIC1206HP4R7MF



PIC1206HP5R6MF




PIC1206HP6R8MF




NOTE: Specifications subject to change without notice. Please check our website for latest information.


PIC1206HP8R2MF




PIC1206HP100MF




PIC1206HP120MF




PIC1206HP150MF



PIC1206HP180MF




PIC1206HP220MF




NOTE: Specifications subject to change without notice. Please check our website for latest information.


PIC1206HP270MF




PIC1206HP330MF




PIC1206HP470MF




PIC1206HP560MF



PIC1206HP680MF




PIC1206HP820MF




NOTE: Specifications subject to change without notice. Please check our website for latest information.


PIC1206HP101MF



PIC1206HP121MF



PIC1206HP151MF



NOTE: Specifications subject to change without notice. Please check our website for latest information.

8. Soldering Specification

Mildly activated rosin fluxes are preferred. Our terminations are suitable for re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

8-1. IR Soldering Reflow


Recommended temperature profiles for lead free re-flow soldering in Figure 1, Table 1.1 & 1.2 (J-STD-020F).

8-2. Iron Reflow

Products attachment with a soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended (Figure 2).


Note:

- (a) Preheat circuit and products to 150°C.
- (b) 350°C tip temperature (Max.)
- (c) Never contact the ceramic with the iron tip
- (d) 1.0mm tip diameter (Max.)
- (e) Use a 20 watt soldering iron with tip diameter of 1.0mm
- (f) Limit soldering time to 4~5 sec.



Reflow times: 3 times Max

Figure 1: IR Soldering Reflow



Iron Soldering times : 1 times max

Figure 2: Iron soldering temperature profiles

NOTE: Specifications subject to change without notice. Please check our website for latest information.

Table (1.1) Reflow Profiles

Profile Type:	Pb-Free Assembly
Preheat	
-Temperature Min (T_{smin})	150°C
-Temperature Max (T_{smax})	200°C
-Time (t_s) from (T_{smin} to T_{smax})	60-120seconds
Ramp-up rate (T_L to T_p)	3°C /second max.
Liquids temperature (T_L)	217°C
Time (t_L) maintained above T_L	60-150 seconds
Classification temperature (T_c)	See Table (1.2)
Time (t_p) at $T_c - 5^\circ\text{C}$ (T_p should be equal to or less than T_c .)	< 30 seconds
Ramp-down rate (T_p to T_L)	6°C /second max.
Time 25°C to peak temperature	8 minutes max.

T_p: maximum peak package body temperature, **T_c**: the classification temperature.

For user (customer) **T_p** should be equal to or less than **T_c**.

Table (1.2) Package Thickness/Volume and Classification Temperature (T_c)


	Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
PB-Free Assembly	<1.6mm	260°C	260°C	260°C
	1.6-2.5mm	260°C	250°C	245°C
	≥2.5mm	250°C	245°C	245°C

Reflow is referred to standard IPC/JEDEC J-STD-020F.

8-3. Soldering Volume

Accordingly increasing the solder volume, the mechanical stress to product is also increased. Exceeding solder volume may cause the failure of mechanical or electrical performance. Solder shall be used not to be exceeded as shown in the Figure below.


Minimum fillet height = soldering thickness + 25% product height.



NOTE: Specifications subject to change without notice. Please check our website for latest information.


9. Packaging Information

9-1. Reel Dimension (Unit: mm)



Type	A	B	C	D	E
13"x24mm	24.4 Ref	100.0 Ref	13.0 Ref	330.0 Ref	2.0 Ref

9-2. Tape Dimension (Unit: mm)




B0	Bz	A0	Az	K0	P	W
14.10±0.10	13.00±0.10	12.90±0.10	7.00±0.10	6.50±0.10	16.00±0.10	24.00±0.30
F	T	E	M	N	D	C
11.50±0.10	0.35±0.05	1.75 Ref	4.00 Ref	2.00 Ref	1.50 Ref	3°

NOTE: Specifications subject to change without notice. Please check our website for latest information.

9-3. Packaging Quantity (Unit: Pcs)

Chip/ Reel	500
Inner box	1,000
Carton	4,000

9-4. Tearing Off Force



The force for tearing off cover tape is according to the follow table, in the arrow direction under the following conditions.

(Referenced ANSI/EIA-481-D-2008 of 4.11 standard)

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed (mm/min)
5~35	45~85	860~1060	300±10

Tape Size	8 mm	12 to 56 mm	72 mm or Wider
Tearing Off Force (grams)	10~100	10~130	10~150

Application Notice

1. Storage Conditions

To maintain the solderability of terminal electrodes:

- (a) Products meet IPC/JEDEC J-STD-020F standard-MSL, level 1.
- (b) Recommended products should be used within 12 months from the time of delivery.
- (c) The packaging material should be kept where no chlorine or sulfur exists in the air.

2. Transportation

- (a) Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- (b) Vacuum pick up is strongly recommended for individual components.
- (c) Bulk handling should ensure that abrasion and mechanical shock are minimized.

NOTE: Specifications subject to change without notice. Please check our website for latest information.